



# Nebbia

## Ultra-Matte Decorative Coating

High-decoration interior wall finish

Ultra-matte decorative coating characterized by extraordinary tactile softness and a pleasant texture, reminiscent of soft leather and brushed suede.

### COMPOSITION

Inorganic and organic pigments, acrylic copolymers in emulsion, polymeric soft-touch microspheres, special non-toxic additives. Free of harmful substances such as solvents and lead or chromium-based pigments.

### TECHNICAL DATA

#### SPECIFIC WEIGHT

1.103 ± 5% kg/L

#### FILM APPEARANCE

Matte patina

#### RECOMMENDED COATS

2

#### FULL CURE

24–48 hours at 20°C

#### DILUTION

Ready to use

#### COLORS

Color card shades

#### SHELF LIFE

24 months

#### FIRE RATING

Non-flammable

#### HS CODE

32149000

#### VISCOSITY

Brookfield 3000 Cps

#### COVERAGE

5–7 m<sup>2</sup>/L (two coats)

#### TOUCH DRY

4–5 hours at 20°C

#### APPLICATION TEMP

5°C – 30°C

#### RECOMMENDED PRIMER

Quartz Primer

#### PACKAGING

2.5L

#### WASHABILITY

Highly washable after 3 weeks

#### VOC CLASS

French VOC A+

### APPLICATION METHODS

- Pennellato (Brushed)
- Rigato (Striped)
- Spatolato (Troweled)
- Broccato (Brocade)